

LED line PRIME

Code: 206670

EAN: 5905378206670

LED line PRIME LED strip 624 COB 24V
2700K-6500K CCT 14W



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	90 lm/W	LED type	COB
Colour of the light	CCT-3pin	LED quantity	624
Energy efficiency class 2019/2015	G	Not dimmable	TAK
Luminous flux	1260 lm	Compatible dimmer type	PWM
Colour consistency in McAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	2
Warranty (years)	5	LED quantity (lm)	624
Dimmable function	PWM	Type of adhesive tape	3M 300 LSE
Survival factor	0.9	Number of on/off cycles	50000
Minimum purchase quantity	5	Colour consistency in McAdam ellipses	≤3
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-20÷45 °C
Wire length	140 mm	For indoor use	Inside
PCB width	10 mm	IEC protection class	III
Wattage (lm)	14 W	Lamp's warm-up time to 60%	1
Luminous flux (lm)	740lm	Width	10 mm
Current (lm)	0,583	Height	2,1 mm
Colour rendering index Ra	90	Energy class	A+
CRI colour rendering index	90		
Metres per roll	5	Power	• 14
The lumen maintenance factor	96 %	Voltage	• 24 V DC
Beam angle	120 °	Correlated colour temperature	• 2700-6500 K

LED line PRIME

Code: 206670


EAN: 5905378206670

LED line PRIME LED strip 624 COB 24V
2700K-6500K CCT 14W


Dimensions

Light distribution

Additional product photos




Logistics data




Single packaging

Width	153 mm
Height	15 mm
Length	153 mm
Weight	0,16 kg
	5



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm
Height of collective packaging	180 mm
Length	320 mm
Weight	6,6 kg
Volume	0,020 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	300 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line PRIME

Code: 206670

EAN: 5905378206670

**LED line PRIME LED strip 624 COB 24V
2700K-6500K CCT 14W**

Example application