

LED line LITE

Code: 202856

EAN: 5905378202856

LED line LITE Downlight EASY FIX PRO
24W 2400lm CCT 3000-5000K round



Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	Material (cover)	polycarbonate
Colour of the light	White	LED type	SMD2835
Energy efficiency class 2019/2015	E	LED quantity	224
Luminous flux	2400 lm	Power Factor	0,7
Colour consistency in McAdam ellipses	≤6	Number of on/off cycles	20000
IP protection rating	IP20	Colour consistency in McAdam ellipses	≤6
Warranty (years)	3	Ambient temperature suitable for operation	-20÷40 °C
Dimmable function	PWM	Mounting hole diameter	60-250 mm
Survival factor	0,9	For indoor use	Inside
Lifetime L70B50	25 000	IEC protection class	II
Weight	750 g	IK protection rating	05
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	85	Height	19,5 mm
Colour	White	Power	• 24 W
The lumen maintenance factor	96 %	Voltage	• 220-240 V AC
Beam angle	110 °	Correlated colour temperature	• 3000 K • 4000 K • 5000 K

LED line LITE

Code: 202856



EAN: 5905378202856

LED line LITE Downlight EASY FIX PRO
24W 2400lm CCT 3000-5000K round




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	306 mm
Height	40 mm mm
Length	296 mm mm
Weight	0,8 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	10 szt.
Width	432 mm mm
Height of collective packaging	315 mm
Length	327 mm mm
Weight	10 kg kg
Volume	0,044 m3 m3

Europallet

Quantity collective euro pallet	240 szt.
Weight of a euro pallet	240 kg
Pallet height	1890 mm
Quantity in 1 layer	40 szt.
Number of layers	6

LED line LITE

Code: 202856

EAN: 5905378202856

**LED line LITE Downlight EASY FIX PRO
24W 2400lm CCT 3000-5000K round**

Example application