

LED line PRIME

Code: 216334

EAN: 5905378216334


PHANTOM 200W 4000K 190lm/W
38000lm DALI 60° PRIME



Phantom PRIME is a high-performance high-bay luminaire that combines energy efficiency, reliability, and ease of installation. Designed with warehouses, sports facilities, and food or pharmaceutical plants in mind, it ensures excellent working conditions and quick return on investment.

Key features:

- Power: 70 W / 100 W / 150 W / 200 W, efficiency up to 190 lm/W (CRI 70) or 175 lm/W (CRI 80)
- Adjustable beam angles: 60° / 90° / 120° for precise illumination
- PZH certificate – approved for environments with strict hygiene requirements
- Smart dimming (1-10 V) with Merrytek sensors or via DALI2
- IP65 & IK08 protection, operating temperature from -30 °C to +45 °C
- Lightweight aluminum housing – quick and safe high-level installation
- 5-year warranty – full service support



Technical data

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5
Power	• 200 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP65
IK protection rating	08
IEC protection class	I
Luminous efficacy	190
Luminous flux	38000

Parameter	Value
The lumen maintenance factor	96
Lifetime L70B50	100 000 h
Dimmable function	Dali
Frequency of the supply voltage	50/60Hz
Fixture's diameter	330 mm
Beam angle	60
LED type	SMD 2835
LED quantity	640
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-30÷45
Material (housing)	Aluminium


LED line PRIME

Code: 216334

EAN: 5905378216334



**PHANTOM 200W 4000K 190lm/W
38000lm DALI 60° PRIME**

Technical drawing




Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 216334

EAN: 5905378216334

**PHANTOM 200W 4000K 190lm/W
38000lm DALI 60° PRIME**

Example application

