


### code: 245343 EAN: 5901583245343

## LED line® UFO T-Series 100-277V 150W 22500LM 4000K 60° DIM





High luminous efficacy ensured by high quality CREE branded LEDs.



Manufacturer issues a 5-year warranty for this product.

tests performed at the LED line® Light Research and



which ensures reliable and fault-free operation even during prolonged, continous running. FLICKER FREE™ system guarantees no harmful flickering

effect and ensures safety for users' eyesight.

This product is equipepd with a MEANWELL branded driver

Beam angle



Ambient temperature suitable for operation



Lifespan

Dimmable

Parameter	Value
Luminous efficacy	150 lm/W
Power	150 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	22500 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	65
Warranty (years)	5
Dimmable function	1-10
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	100-277 VAC
Frequency of the supply voltage	50/60Hz

LED line® export@ledline.pl www.ledline.pl/en

Wygenerowano 05-02-2025 godz 18:02 z systemu PIM B2B - LED Line



Measurement Centre.

Reliable photometric files are available based on photometric





00-277 VA

SMD3030

216

The power supply system used allows for smooth adjustment of light intensity using an appropriate dimmer.

Voltage range and voltage type

LED type

LED quantity

Parameter	Value
Material (housing)	aluminum
LED type	SMD3030
LED quantity	216
Not dimmable	ТАК
Compatible dimmer type	1-10V
Lifespan	50000
Power Factor	0,95
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-40÷45 °C
For indoor and outdoor use	YES
IEC protection class	I
IK protection rating	08
Full box quantity	1 pc




Colour rendering index Ra	70
Colour	black
The lumen maintenance factor	96 %
Lamp's diameter	260
Beam angle	60 °
Material (cover)	polycarbonate

Lamp's warm-up time to 60%	1
Height	250 mm
Product weight with packaging	4150 g
Master carton weight (kg)	41,5
Energy class	A+

# Luminous [cd/klm]


**C0 - C180 C90 - C270** 

### Single packaging




Width Height Length Weight 330 mm 215 mm 330 mm 4,66 kg 1

### Bulk packaging



Width Length Weight Volume 1 330 mm 215 330 mm 4,66 kg 0,023 m3 Europallet



Weight of a euro pallet