


LED line PRIME

Code: LL-200-12

EAN: 5907777479341

Power Supply 200-12 IP67 200W 12V PRIME

The PRIME 200-12 IP67 LED line power supply is a high-performance power supply offering a stable 12V output voltage and 192W power. Designed to work in difficult conditions, it is characterized by IP67 class of leaks, which provides protection against water and dust. With a rated current of 16A and efficiency of 84%, the device guarantees effective operation. The power supply is compatible with PN-EN IEC and EN55015 standards, which confirms its safety and reliability in use.



Technical data

Parameter	Value
Warranty	5
Power	• 192 W
Voltage	• 200-264 V AC
IEC protection class	II
Output current range	0 ÷ 16A
Input voltage frequency range	47 ÷ 63Hz
Rated current	16A
Safety standards	IP67
Efficiency	0,84

Parameter	Value
Voltage tolerance	-/+5,0%
Ambient humidity	20 ÷ 95%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	30A / 230VAC
Ambient temperature suitable for operation	-30÷70
Output voltage	• 12 V


LED line PRIME

Code: LL-200-12

EAN: 5907777479341


**Power Supply 200-12 IP67 200W 12V
PRIME**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	85 mm
Height	55 mm
Length	280 mm
Weight	1,17 kg

Bulk packaging

Quantity	15
Width	295 mm
Height	190 mm
Length	455 mm
Weight	18,5 kg

Europallet

Quantity	480
Height	1,90 m
Quantity in layer	160
Number of layers	3
Bulk quantity	32
Weight	913 kg

LED line PRIME

Code: LL-200-12

EAN: 5907777479341

**Power Supply 200-12 IP67 200W 12V
PRIME**

Example application