

LED line PRIME


Code: 478962

EAN: 5907777478962

**Linear luminaire FUSION 4000K 60W  
7800lm P18° IP20 150cm black PRIME**



FUSION 60W LED line PRIME and 4000K colour temperature provides an intense light stream of 7800 lumens. It is characterized by a high energy efficiency of 130 lm/W and a power factor PF 0.9. The angle of light distribution is 120° and the use of lenses allows to adjust its direction. A body made of aluminium guarantees excellent heat discharge.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 60 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	08
IEC protection class	I
Luminous efficacy	130
Luminous flux	7800
The lumen maintenance factor	96

Parameter	Value
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Sling length	200 cm
Standby power	0
Mounting type	mixed
Frequency of the supply voltage	50/60Hz
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
For indoor use	Inside
Height	52


LED line PRIME

Code: 478962


EAN: 5907777478962

**Linear luminaire FUSION 4000K 60W  
7800lm P18° IP20 150cm black PRIME**

**Technical drawing**






**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Width	1444 mm
Height	52 mm
Length	70 mm
Weight	1,97 kg

**Bulk packaging**

Quantity	12
Width	1550 mm
Height	260 mm
Length	260 mm
Volume	0,104 m3
Weight	23,89 kg
Comments	

**Europallet**

Quantity	144
Height	1550 mm
Quantity in layer	144
Number of layers	1
Bulk quantity	144
Weight	286,8 kg

---

LED line PRIME

Code: 478962

EAN: 5907777478962

**Linear luminaire FUSION 4000K 60W  
7800lm P18° IP20 150cm black PRIME**

---

**Example application**