

LED line LITE

Code: 240133

EAN: 5901583240133

**LED strip 150/5m SMD 12V YELLOW
2,4W IP65 8mm 5m LITE**

LED line 150 SMD 12V in yellow with a power of 2.4 In this efficient lighting solution. It is characterized by effective SMD3528 diodes, offering long-term operation and low energy consumption. Thanks to a wide light angle of 120°, the tape ensures uniform light scattering. The stability of the assembly guarantees high quality 3M adhesive and flexible white laminate.



Technical data

Parameter	Value
Warranty	3
Power	• 2.4 W / m
Voltage	• 12 V DC
Colour of the light	Yellow
IEC protection class	III
Cutting section	10 cm
The lumen maintenance factor	>0,7
Lifetime L70B50	30 000 h
Dimmable function	PWM
Current (Im)	0,2
Beam angle	120

Parameter	Value
LED type	SMD3528
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	30
Type of adhesive tape	3M 300 LSE
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
Height	3

LED line LITE


Code: 240133

EAN: 5901583240133

**LED strip 150/5m SMD 12V YELLOW
2,4W IP65 8mm 5m LITE**




Technical drawing

Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	5 m
Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,167 kg

Bulk packaging

Quantity	40
Width	320 mm
Height	180 mm
Length	360 mm
Volume	0,020 m ³
Weight	6,76 kg
Comments	

Europallet

Quantity	12000 m
Height	1800 mm
Quantity in layer	240
Number of layers	10
Bulk quantity	2400

LED line LITE

Code: 240133

EAN: 5901583240133

**LED strip 150/5m SMD 12V YELLOW
2,4W IP65 8mm 5m LITE**

Example application