

LED line LITE

Code: 240263

EAN: 5901583240263

LED line® strip 300 SMD 12V 11000K
4,8W IP65




Technical data

Parameter	Value	Parameter	Value
Luminous efficacy	83 lm/W	Laminate (colour)	White
Colour of the light	White	Laminate (thickness)	2
Energy efficiency class 2019/2015	G	LED quantity (lm)	60
Colour consistency in MacAdam ellipses	≤6	Cutting section	5
Warranty (years)	3	Type of adhesive tape	3M 300 LSE
Dimmable function	PWM	Lifespan	100000
Survival factor	0.9	Number of on/off cycles	50000
Minimum purchase quantity	5	Colour consistency in MacAdam ellipses	≤6
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-20÷45 °C
Wattage (lm)	4,8 W	For indoor and outdoor use	YES
Luminous flux (lm)	400lm	IEC protection class	III
Current (lm)	0,4	Full box quantity	75 pc
Colour rendering index Ra	80	Lamp's warm-up time to 60%	1
Metres per roll	5	Width	8 mm
The lumen maintenance factor	96 %	Height	3 mm
Beam angle	120 °	Energy class	A+
LED type	SMD3528	Power	• 4.8
Not dimmable	TAK	Voltage	• 12 V DC
Compatible dimmer type	PWM	Correlated colour temperature	• 11000 K


LED line® strip 300 SMD 12V 11000K
4,8W IP65

Dimensions


Light distribution



Additional product photos




Logistics data




Single packaging

Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,19 kg
1	



Bulk packaging

Number of pieces/tape in meters pack zb	40 szt.
Width	360 mm mm
Height of collective packaging	180 mm
Length	320 mm mm
Weight	7,66 kg kg
Volume	0,020 m3 m3



Europallet

Number of pieces/tapes in meters euro pallet	12000 m
Quantity collective euro pallet	2400 szt.
Weight of a euro pallet	484,6 kg
Pallet height	1800 mm
Quantity in 1 layer	240 szt.
Number of layers	10

LED line LITE

Code: 240263

EAN: 5901583240263

**LED line® strip 300 SMD 12V 11000K
4,8W IP65**

Example application