

LED line LITE LED bulb E27 10W 2700K 1200lm 220-240V FILAMENT A60 GLOBE



Manufacturer issues a 3-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



LED type



High user-safety guaranteed.



Voltage range and voltage type



Lamp type



Lifespan



LED quantity

Parameter	Value
Luminous efficacy	120 lm/W
Power	10 W
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	1200 lm
Correlated colour temperature	2700 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	3
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	25 000
Weight	35 g
Supply voltage range and voltage type	220-240V
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96
Lamp's type	A60
Lamp's diameter	60
Beam angle	360 °

Parameter	Value
Lifespan	25000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Full box quantity	50 pc
Lamp's warm-up time to 60%	1
Height	108 mm
Product weight with packaging (g)	50 g
Master carton weight (kg)	3,5
EPREL ID	1 596 594
Date of first placement on the market	2023-11-02 05:38:11
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	7
Total luminous flux (EPREL)	1 200
On-mode power Pon (EPREL)	10

Material (cover)	glass
LED type	Filament
LED quantity	4

Useful luminous flux Φ_{use} (EPREL)	1200
Beam angle in degrees (EPREL)	360

Single packaging



61
110
61
50
1

Bulk packaging



50

Europallet

