

LED line PRIME

Code: 203457-AW3HAT

EAN: 5905378219861

Panel Backlit 42W 4000K 6300lm
UGR<19 60x60 Emergency module
PRIME LAW3HAT



The 42W backlit LED panel and 4000K colour temperature provide exceptional light performance, reaching a light stream of 6300 lm. With low UGR value<19, this model minimizes glare. Made of high quality aluminum and polystyrene, it guarantees longevity and aesthetic appearance. The integrated emergency module allows to operate for 3 hours in case of power interruption.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	B
Warranty	5
Power	<ul style="list-style-type: none">42 W
Voltage	<ul style="list-style-type: none">220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none">4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	150
Luminous flux	6300
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9
Dimmable function	PWM

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Emergency module test	Auto Test
Operating time in emergency mode	3 h
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	108
Power Factor	0,9
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene

LED line PRIME

Code: 203457-AW3HAT


EAN: 5905378219861

**Panel Backlit 42W 4000K 6300lm
UGR<19 60x60 Emergency module
PRIME LAW3HAT**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 203457-AW3HAT

EAN: 5905378219861

**Panel Backlit 42W 4000K 6300lm
UGR<19 60x60 Emergency module
PRIME LAW3HAT**

Example application