

LED line LITE Code: 209954 EAN: 5905378209954

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1050lm round black





The round downlight EASY FLEX 9-12-15W CCT with a power of 1050 lm is characterized by its versatility thanks to the choice of three colour temperatures: 3000 K, 4000 K and 5000 K, which allows to adjust lighting to different needs. It has an E energy class and a Ra colour reproduction factor of 80, which ensures good light quality.



Technical data

Parameter	Value
Voltage	• 220-240 V AC
Luminous efficacy	70
Energy efficiency class 2019/2015	E
Luminous flux	1050
Colour consistency in McAdam ellipses	≤ 6
Warranty (years)	3
IP protection rating	IP20
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	Black
The lumen maintenance factor	96
Fixture's diameter	170

Parameter	Value
Beam angle	120
LED type	SMD2835
LED quantity	84
Number of on/off cycles	15000
Colour consistency in McAdam ellipses	≤ 6
Ambient temperature suitable for operation	-20÷40
Installation method	3in1 surface mounted, flush mounted, suspended
Mounting hole diameter	65-130
IEC protection class	II
IK protection rating	05
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	3000 K4000 K5000 K
Power	• 9 W • 12 W • 15 W




LED line LITE Code: 209954 EAN: 5905378209954

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1050lm round black

Technical drawing

Light distribution

Luminous [cd/klm]



Additional product photos












Logistics data







Single packaging

Bulk packaging

Europallet

MORE EFFICIENCY FOR THE LED WORLD



LED line LITE Code: 209954 EAN: 5905378209954

LED line LITE Downlight EASY FLEX 9-12-15W CCT 1050lm round black

Example application