

LED line PRIME

Code: 476852

EAN: 5907777476852

LED line strip 600 SMD 24V 2700K
14,4W



3-step
MacAdam

YELLOW
FREE™

*.IES
↓

5-year
warranty

product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	100 lm/W	LED type	SMD2835
Colour of the light	White	LED quantity	600
Energy efficiency class 2019/2015	F	Compatible dimmer type	PWM
Colour consistency in McAdam ellipses	≤3	Laminate (colour)	White
IP protection rating	IP20	Laminate (thickness)	3
Warranty (years)	5	LED quantity (lm)	120
Dimmable function	PWM	Cutting section	5
Survival factor	0.9	Type of adhesive tape	3M 300 LSE
Minimum purchase quantity	5	Colour consistency in McAdam ellipses	≤3
Lifetime L70B50	50 000	Ambient temperature suitable for operation	-25÷45 °C
Wire length	200 mm	For indoor use	Inside
Wattage (lm)	14,4 W	IEC protection class	III
Luminous flux (lm)	1440	Length	5000 mm
Current (lm)	0,6	Width	10 mm
Colour rendering index Ra	80	Height	1,3 mm
Metres per roll	5	Energy class	A++
The lumen maintenance factor	96 %	Voltage	• 24 V DC
Beam angle	120 °	Correlated colour temperature	• 2700 K

LED line PRIME


Code: 476852

EAN: 5907777476852


LED line strip 600 SMD 24V 2700K
14,4W

product_card.label_dimensions




product_card.label_curve_light



product_card.label_product_gallery



product_card.label_logistic_data



Single packaging

Width	260
Height	230 mm
Length	303 mm
Weight	3,9 kg
	100

Bulk packaging

Number of pieces/tape in meters pack zb	100
Width	472 mm
Height of collective packaging	280
Length	620 mm
Weight	15,6 kg
Volume	0,08 m3

Europallet

Number of pieces/tapes in meters euro pallet	2400
Quantity collective euro pallet	60
Weight of a euro pallet	300 kg
Pallet height	1800
Quantity in 1 layer	6
Number of layers	10

LED line PRIME

Code: 476852

EAN: 5907777476852

**LED line strip 600 SMD 24V 2700K
14,4W**

Example application