

LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.

LED line® strip 210 SMD 12V RGB 10W

code: 246500 EAN: 5901583246500

TWIST





Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.

LED line $\ensuremath{\mathbb{R}}$ TWIST strip can be bent in any direction without any



Voltage range and voltage type

Ambient temperature suitable for operation

risk of any damage to the laminate.

50 000 h L70B50

мах

Lifespan

Dimmable

Parameter	Value
Colour of the light	RGB
IP protection rating	20
Warranty (years)	5
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (Im)	10 W
Current (Im)	0,83
Supply voltage range and voltage type	12 DC
Metres per roll	5
Beam angle	120 °
LED type	SMD5050
Not dimmable	ТАК
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2

Parameter	Value
LED quantity (1m)	42
Cutting section	7,1
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Ambient temperature suitable for operation	`-20 ÷ 45 ℃
For indoor use	Inside
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	12 mm
Height	2,5 mm
Product weight with packaging (g)	147 g
Master carton weight (kg)	11,03



Manufacturer issues a 5-year warranty for this product.



RGB


Beam angle

LED type


LED quantity (1m)

Luminous [cd/klm]

Single packaging



Bulk packaging



Europallet

