

LED line PRIME

Code: 218284

EAN: 5905378218284

**Track light Linear LUMICANTO 30-42W
3CCT(3K/4K/6K) 90° IP20 120cm black
PRIME**



The linear fixture **Lumicanto Linear** for a 3-phase track combines modern design with maximum usability. It stands out with the ability to adjust the beam angle by 20 degrees and an ultra-low adapter that perfectly aligns with the track, providing an aesthetic ceiling appearance. The fixture allows for easy configuration of parameters thanks to power switches (4 ranges - 30/34/38/42W) and light color (3CCT - 3000K/4000K/6000K). A high Ra90 coefficient and luminous efficacy of 120 lm/W make it an ideal choice for offices and retail spaces.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	<ul style="list-style-type: none"> • 30 W • 34 W • 38 W • 42 W
Voltage	<ul style="list-style-type: none"> • 220-240 V AC
Correlated colour temperature	<ul style="list-style-type: none"> • 3000-4000-6000 K
Colour of the light	CCT
Colour rendering index Ra	90
IP protection rating	IP20
IK protection rating	02
IEC protection class	I
Luminous efficacy	120
Luminous flux	5000

Parameter	Value
Lifetime L70B50	60 000 h
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD 2835
LED quantity	192
Power Factor	0,9
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Height	45 mm
Colour	black

LED line PRIME


Code: 218284

EAN: 5905378218284

**Track light Linear LUMICANTO 30-42W
3CCT(3K/4K/6K) 90° IP20 120cm black
PRIME**

Technical drawing




Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	
Width	55 mm
Height	75 mm
Length	1205 mm
Weight	1,6 kg

Bulk packaging

Quantity	10
Width	290 mm
Height	170 mm
Length	1220 mm
Weight	15,2 kg

Europallet

Quantity	160
Height	140 cm
Quantity in layer	160
Number of layers	1
Bulk quantity	16
Weight	270 kg

LED line PRIME

Code: 218284

EAN: 5905378218284

**Track light Linear LUMICANTO 30-42W
3CCT(3K/4K/6K) 90° IP20 120cm black
PRIME**

Example application

