


## LED line LITE LED Bulb E27 6W 3000K 510lm 230V G45



Beam angle



Ambient temperature suitable for operation



Voltage range and voltage type




Lifespan

Parameter	Value
Luminous efficacy	85 lm/W
Power	6 W
Colour of the light	White
Energy efficiency class 2019/2015	F
Luminous flux	510 lm
Correlated colour temperature	3000 K
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
Survival factor	0.9
Lifetime L70B50	50 000
Supply voltage range and voltage type	220-240 VAC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96 %


Parameter	Value
Lamp's diameter	45
Beam angle	240 °
Material (housing)	PVC
Lifespan	50000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
For indoor use	Inside
Full box quantity	10 pc
Height	84 mm
Product weight with packaging	19 g
Energy class	A+

**Single packaging**




Width	50 mm
Height	59 mm
Length	50 mm
Weight	0,03 kg
	1

**Bulk packaging**



Number of pieces/tape in meters pack zb	100 szt.
Width	475 mm
Height of collective packaging	190 mm
Length	245 mm
Weight	3,5 kg
Volume	0,022 m <sup>3</sup>

**Europallet**



Number of pieces/tapes in meters euro pallet	5600
Quantity collective euro pallet	6000 szt.
Weight of a euro pallet	210 kg
Pallet height	1900 mm
Quantity in 1 layer	600 szt.
Number of layers	10