


LED line® strip 600 SMD 12V red 9,6W

Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Manufacturer issues a 5-year warranty for this product.



Beam angle



Voltage range and voltage type



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity (1m)




Dimmable


Parameter	Value
Colour of the light	Red
IP protection rating	20
Warranty (years)	5
Dimmable function	PWM
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (1m)	9,6 W
Current (1m)	0,8
Supply voltage range and voltage type	12 VDC
Metres per roll	5
The lumen maintenance factor	>0,7 %
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White

Parameter	Value
Laminate (thickness)	2
LED quantity (1m)	120
Cutting section	2,5
Type of adhesive tape	3M 300 LSE
Lifespan	100000
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤3
Ambient temperature suitable for operation	-20÷45 °C
For indoor use	Inside
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	2,5 mm
Product weight with packaging	117 g
Master carton weight (kg)	8,78


Luminous [cd/klm]



Single packaging




Bulk packaging



Number of pieces/tape in meters pack zb 100

Europallet



Number of pieces/tapes in meters euro pallet	
Quantity collective euro pallet	24
Pallet height	984
Quantity in 1 layer	8
Number of layers	3