

LED line LITE


Code: 209848

EAN: 5905378209848

Park Luminaire PARKLITE 50W CCT 6000lm grey LITE

New

PARKLITE 50W CCT Park luminaire offers exceptional power of 50 W and a light stream of 6000 lm, which provides excellent lighting performance. Its construction materials, including aluminium and tempered glass, guarantee high resistance to damage (IK08) and effective protection against atmospheric conditions (IP65). The lamp is characterized by high energy efficiency with a power factor PF 0.9.



Technical data

Parameter	Value
ULOR	2,3 %
Voltage	• 220-240 V AC
Luminous efficacy	120
Luminous flux	6000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	3
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	25 000 h
Wire length	400 mm
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
The lumen maintenance factor	96

Parameter	Value
Beam angle	100
Material (cover)	tempered glass
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	384
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-30°C ~ +50°C
IEC protection class	I
IK protection rating	08
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	• 3000 K • 4000 K • 6000 K
Power	• 50 W

LED line LITE


Code: 209848

EAN: 5905378209848


**Park Luminaire PARKLITE 50W CCT  
6000lm grey LITE**

**Technical drawing**


**Light distribution**




**Additional product photos**




**Logistics data**



**Single packaging**



**Bulk packaging**



**Europallet**

---

LED line LITE

Code: 209848

EAN: 5905378209848

**Park Luminaire PARKLITE 50W CCT  
6000lm grey LITE**

---

**Example application**