

LED line PRIME

Code: LL-12-12

EAN: 5907777479167

Power Supply 12-12 IP67 12W 12V PRIME

The PRIME 12-12 IP67 12V LED line power supply is a high quality 12W output power device and a wide input voltage range from 90 to 264 V AC. It offers stable operation with rated current of 1 A and efficiency of 0.76. The product has IP67 protection class, which provides water and dust resistance. Additionally, the power supply meets a number of safety standards, including EN55015 and PN-EN IEC 61000-3-2.



Technical data

| Parameter | Value |
|-------------------------------|---------------|
| Warranty | 5 |
| Power | • 12 W |
| Voltage | • 90-264 V AC |
| IEC protection class | II |
| Output current range | 0 ÷ 1A |
| Input voltage frequency range | 47 ÷ 63Hz |
| Rated current | 1A |
| Safety standards | IP67 |
| Efficiency | 0,76 |

| Parameter | Value |
|--|-------------|
| Voltage tolerance | -/+5.0% |
| Ambient humidity | 20 ÷ 90% |
| Insulation strength | 3kVAC |
| EMC standards | EN55015 |
| Mounting type | surface |
| Inrush current (typ.) | 6A / 230VAC |
| Ambient temperature suitable for operation | -30÷70 |
| Output voltage | • 12 V |


LED line PRIME

Code: LL-12-12

EAN: 5907777479167


Power Supply 12-12 IP67 12W 12V PRIME

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

| | |
|----------|---------|
| Quantity | 1 |
| Width | 41 mm |
| Height | 27 mm |
| Length | 165 mm |
| Weight | 0,13 kg |

Bulk packaging

| | |
|----------|---------|
| Quantity | 100 |
| Width | 290 mm |
| Height | 230 mm |
| Length | 345 mm |
| Weight | 14,5 kg |

Europallet

| | |
|---------------|---------|
| Quantity | 3200 |
| Height | 1020 mm |
| Bulk quantity | 32 |
| Weight | 474 kg |

LED line PRIME

Code: LL-12-12

EAN: 5907777479167

Power Supply 12-12 IP67 12W 12V PRIME

Example application