

LED line PRIME

Code: LL-60-12

EAN: 5905378200159

**Power Supply 60-12 IP67 60W 12V PRIME**

The PRIME 60-12 IP67 LED line power supply is an advanced 60W output power device designed to operate in difficult conditions. It offers an output voltage of 12V at a stable nominal current of up to 5A. Thanks to IP67, it effectively protects against water and dust, which ensures reliability in different environments. The product has a high efficiency of 84%, which translates into energy efficiency.



**Technical data**

Parameter	Value
Warranty	5
Power	• 60 W
Voltage	• 90-264 V AC
IEC protection class	II
Output current range	0 ÷ 5A
Input voltage frequency range	50 ÷ 60Hz
Rated current	0,275
Safety standards	IP67
Efficiency	0,84
Voltage tolerance	-/+5.0%

Parameter	Value
Ambient humidity	20 ÷ 90%
Insulation strength	3kVAC
EMC standards	EN55015
Mounting type	surface
Inrush current (typ.)	70A / 230VAC
Power Factor	>=0,95
Ambient temperature suitable for operation	-30÷40
Height	33 mm
Output voltage	• 12 V


LED line PRIME

Code: LL-60-12

EAN: 5905378200159


**Power Supply 60-12 IP67 60W 12V  
PRIME**

**Technical drawing**






**Light distribution**

**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	52 mm
Height	35 mm
Length	185 mm
Weight	0,42 kg

**Bulk packaging**

Quantity	40
Width	205 mm
Height	215 mm
Length	385 mm
Weight	17,3 kg

**Europallet**

Quantity	2400
Height	1,90 m
Quantity in layer	
Number of layers	
Bulk quantity	60
Weight	1100 kg

---

LED line PRIME

Code: LL-60-12

EAN: 5905378200159

**Power Supply 60-12 IP67 60W 12V  
PRIME**

---

**Example application**