

LED line PRIME

Code: 203457

EAN: 5905378203457

LED line PRIME Panel Backlit 42W
4000K 6300lm UGR<19 595x595



product_card.label_technical_data

Parameter	Value	Parameter	Value
Luminous efficacy	150 lm/W	Material (housing)	aluminum
Colour of the light	White	LED type	SMD LED 2835
Energy efficiency class 2019/2015	B	LED quantity	108
Luminous flux	6300 lm	Power Factor	0,9
Colour consistency in McAdam ellipses	≤6	Number of on/off cycles	25000
IP protection rating	IP20	Colour consistency in McAdam ellipses	≤6
Warranty (years)	5	Ambient temperature suitable for operation	-25÷45 °C
Dimmable function	PWM	For indoor use	Inside
Survival factor	0.9	IEC protection class	II
Lifetime L70B50	50 000	IK protection rating	02
Frequency of the supply voltage	50/60Hz	Lamp's warm-up time to 60%	1
Colour rendering index Ra	80	Height	28 mm
Colour	White	Power	• 42 W
The lumen maintenance factor	96 %	Voltage	• 220-240 V AC
Beam angle	90 °	Correlated colour temperature	• 4000 K
Material (cover)	polystyrene		

LED line PRIME

Code: 203457


EAN: 5905378203457

LED line PRIME Panel Backlit 42W
4000K 6300lm UGR<19 595x595




product_card.label_dimensions

product_card.label_curve_light

product_card.label_product_gallery



product_card.label_logistic_data



Single packaging

Width	645 mm
Height	30 mm mm
Length	605 mm mm
Weight	1,68 kg kg
	1

Bulk packaging

Number of pieces/tape in meters pack zb	5 szt.
Width	630 mm mm
Height of collective packaging	670 mm
Length	180 mm mm
Weight	10,4 kg kg
Volume	0,075 m3 m3

Europallet

Quantity collective euro pallet	60 szt.
Weight of a euro pallet	124,8 kg
Pallet height	1340 mm
Quantity in 1 layer	30 szt.
Number of layers	2

LED line PRIME

Code: 203457

EAN: 5905378203457

LED line PRIME Panel Backlit 42W
4000K 6300lm UGR<19 595x595

Example application