

LED line PRIME

Code: 203457

EAN: 5905378203457

**Backlit Panel 4000K 42W 6300lm IP20
60x60cm white UGR<19 PRIME**



The PRIME Backlit LED line panel with 42W power and 6300 lm light stream is a modern lighting solution that is characterized by the colour of light 4000K. Low glare rate UGR<19 provides comfort of use in intensely exploited spaces. In standard dimensions 595x595 mm, made of high quality materials, guarantees long-term use and energy efficiency at Class B level.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	C
Warranty	5/7*
Power	• 42 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IK protection rating	02
IEC protection class	II
Luminous efficacy	150
Luminous flux	6300
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
Beam angle	90
LED type	SMD LED 2835
LED quantity	108
Power Factor	>=0,95
Number of on/off cycles	25000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
Height	28 mm
Colour	White
Material (housing)	Aluminium
Material (cover)	Polystyrene


LED line PRIME

Code: 203457


EAN: 5905378203457

**Backlit Panel 4000K 42W 6300lm IP20
60x60cm white UGR<19 PRIME**

Technical drawing





Light distribution



Additional product photos



Logistics data



Single packaging

Quantity	1
Width	645 mm
Height	30 mm
Length	605 mm
Weight	1,68 kg

Bulk packaging

Quantity	5
Width	630 mm
Height	180 mm
Length	670 mm
Volume	0,075 m3
Weight	10,4 kg
Comments	

Europallet

Quantity	60
Height	1,9 m
Quantity in layer	
Number of layers	
Bulk quantity	12
Weight	150 kg

LED line PRIME

Code: 203457

EAN: 5905378203457

**Backlit Panel 4000K 42W 6300lm IP20
60x60cm white UGR<19 PRIME**

Example application