

LED line PRIME

Code: 217591


EAN: 5905378217591

**Solar wall lamp SUNTIS 3000K 220lm
2Ah USB-C square IP54 black PRIME**



The Suntis facade solar fixture from the LED line PRIME brand offers efficient lighting at a color temperature of 3000 K, generating a luminous flux of 220 lumens. Equipped with a 2000 mAh Li-Ion battery, it provides up to 9 hours of operation on a single charge.

Thanks to its IP54 protection class, it is resistant to weather conditions. Its modern, square design made of durable ABS material fits perfectly into outdoor arrangements.



Technical data

Parameter	Value
Warranty	5
Voltage	• 3.7 V DC
Correlated colour temperature	• 3000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP54
IK protection rating	06
IEC protection class	III
Luminous flux	220
Lifetime L70B50	30 000 h
Wyniki tłumaczenia Functional description of the daylight sensor [LUX]	50 lx-ON

Parameter	Value
Type of battery	Li-Ion 3.7V 2000mAh 18650
Beam angle	120
Sensor type	PIR
LED quantity	40
Lifespan	35 000 h
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷40
For indoor use	Outside
Height	80 mm
Colour	Czarny
Material (housing)	ABS


LED line PRIME

Code: 217591

EAN: 5905378217591

**Solar wall lamp SUNTIS 3000K 220lm
2Ah USB-C square IP54 black PRIME**

Technical drawing






Light distribution

Additional product photos



Logistics data



Single packaging

Quantity	1
Width	125 mm
Height	85 mm
Length	125 mm
Weight	0,7 kg

Bulk packaging

Quantity	12
Width	265 mm
Height	200 mm
Length	405 mm
Weight	8,7 kg

Europallet

Height	1,90 m
Quantity in layer	4
Number of layers	8
Bulk quantity	384
Weight	220 kg

LED line PRIME

Code: 217591

EAN: 5905378217591

**Solar wall lamp SUNTIS 3000K 220lm
2Ah USB-C square IP54 black PRIME**

Example application

