


code: 240713 EAN: 5901583240713

## LED line® strip 300 SMD 24V 3000K 4,8W IP65

LED Strip line is a modern and versatile linear **light source**, used for interior lighting, furniture, lightboxes, illuminated signs, and public spaces.



The colour temperature range of the product falls within 3 steps of MacAdam formula, which ensures high consistency of the produced light.



Reliable photometric files are available based on photometric tests performed at the LED line® Light Research and Measurement Centre.



Yellow free technology means that the housing of this product is made of high quality material which is resistant to yellowing degeneration caused by UV radiation, thanks to which the product maintains its esthetic appearance for many years.



This product is featured by a high degree of IP protection, which makes it suitable for a broader range of lighting applications and offers high safety of use.



Manufacturer issues a 3-year warranty for this product.



Voltage range and voltage type



Beam angle



Ambient temperature suitable for operation



LED type



Lifespan



LED quantity (1m)




Dimmable

Parameter	Value
Luminous efficacy	83 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	G
Correlated colour temperature	3000 K
Colour consistency in MacAdam ellipses	≤6
Warranty (years)	3
Dimmable function	Yes
Survival factor	0.9
Minimum purchase quantity	5
Lifetime L70B50	50 000
Wattage (1m)	4,8 W
Luminous flux (1m)	400lm
Current (1m)	0,2
Supply voltage range and voltage type	24 DC
Colour rendering index Ra	80
Metres per roll	5


Parameter	Value
Number of on/off cycles	50000
Colour consistency in MacAdam ellipses	≤6
Ambient temperature suitable for operation	-20 ÷ 45 °C
For indoor use	Inside
IEC protection class	III
Full box quantity	75 pc
Lamp's warm-up time to 60%	1
Width	8 mm
Height	3 mm
Product weight with packaging (g)	192 g
Master carton weight (kg)	14,4
EPREL ID	631 980
Date of first placement on the market	01.09.2021
Energy class	A+
Form of the product (EPREL)	Dotyczy 50cm taśmy
Angle for useful luminous flux (EPREL)	Sphere 360 degrees

The lumen maintenance factor	96
Beam angle	120 °
LED type	SMD3528
Not dimmable	TAK
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (1m)	60
Cutting section	10
Type of adhesive tape	3M 300 LSE
Lifespan	100000

Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	NMLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
R9 colour rendering index value (EPREL)	14
Total luminous flux (EPREL)	200
On-mode power $P_{on}$ (EPREL)	2
Useful luminous flux $\Phi_{use}$ (EPREL)	200
Beam angle in degrees (EPREL)	120




Single packaging




1

Bulk packaging



100

Europallet



6