

LED line LITE


Code: 240713

EAN: 5901583240713

**LED strip 300/5m SMD 24V 3000K 4,8W
IP65 8mm 5m 480lm/m LITE**



LED line 300 SMD 24V 3000K 4.8W IP65 is an innovative lighting solution that is characterized by high quality SMD3528 diodes. It emits a warm, white light with a colour temperature of 3000K, providing a pleasant atmosphere. IP65 protection class protects against moisture and dust, which increases its durability to 100,000 hours.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	G
Warranty	3
Power	• 4.8 W / m
Voltage	• 24 V DC
Colour of the light	White
Colour rendering index Ra	80
IEC protection class	III
Cutting section	10 cm
Luminous efficacy	83
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Dimmable function	PWM
Colour consistency in McAdam ellipses	≤6

Parameter	Value
Luminous flux (lm)	400
Current (Im)	0,2
Beam angle	120
LED type	SMD3528
Compatible dimmer type	PWM
Laminate (colour)	White
Laminate (thickness)	2
LED quantity (lm)	60
Type of adhesive tape	3M 300 LSE
Lifespan	100 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1
Ambient temperature suitable for operation	-20÷45
Height	3


LED line LITE

Code: 240713


EAN: 5901583240713

**LED strip 300/5m SMD 24V 3000K 4,8W
IP65 8mm 5m 480lm/m LITE**

Technical drawing





Light distribution



Additional product photos

Logistics data



Single packaging

Quantity	5 m
Width	180 mm
Height	20 mm
Length	180 mm
Weight	0,167 kg
Comments	

Bulk packaging

Quantity	40
Width	360 mm
Height	180 mm
Length	320 mm
Volume	0,020 m ³
Weight	7,66 kg
Comments	

Europallet

Quantity	12000 m
Height	1800 mm
Quantity in layer	240
Number of layers	10
Bulk quantity	2400
Weight	300 kg

LED line LITE

Code: 240713

EAN: 5901583240713

**LED strip 300/5m SMD 24V 3000K 4,8W
IP65 8mm 5m 480lm/m LITE**

Example application