

LED line

Code: 241826

EAN: 5901583241826

LED line strip 150 SMD 12V 4000K 2,4W



product_card.label_technical_data

Parameter	Value	Parameter	Value
Colour of the light	White	Laminate (colour)	White
Energy efficiency class 2019/2015	G	Laminate (thickness)	2
Luminous flux	200 lm	LED quantity (lm)	30
Colour consistency in McAdam ellipses	≤3	Cutting section	10
IP protection rating	IP20	Type of adhesive tape	3M 300 LSE
Warranty (years)	5	Lifespan	100000
Dimmable function	PWM	Number of on/off cycles	50000
Survival factor	0.9	Colour consistency in McAdam ellipses	≤3
Minimum purchase quantity	5	Ambient temperature suitable for operation	-20 ÷ 45 °C
Lifetime L70B50	50 000	For indoor use	Inside
Wattage (lm)	2,4 W	IEC protection class	III
Current (lm)	0,2	Full box quantity	75 pc
Colour rendering index Ra	80	Lamp's warm-up time to 60%	1
Metres per roll	5	Width	8 mm
The lumen maintenance factor	96 %	Height	2,5 mm
Beam angle	120 °	Energy class	A++
LED type	SMD3528	Voltage	• 12 V DC
Not dimmable	TAK	Correlated colour temperature	• 4000 K
Compatible dimmer type	PWM		

LED line


Code: 241826

EAN: 5901583241826


LED line strip 150 SMD 12V 4000K 2,4W

product_card.label_dimensions


product_card.label_curve_light



product_card.label_product_gallery




product_card.label_logistic_data




Single packaging

1



Bulk packaging

Number of pieces/tape in meters pack zb	100
Width	340 mm
Height of collective packaging	280
Length	440 mm
Weight	0,1 kg
Volume	0,042 m3



Europallet

Number of pieces/tapes in meters euro pallet	2400
Quantity collective euro pallet	60
Weight of a euro pallet	300 kg
Pallet height	1800
Quantity in 1 layer	6
Number of layers	10

LED line

Code: 241826

EAN: 5901583241826

LED line strip 150 SMD 12V 4000K 2,4W

Example application