

LED line PRIME

Code: 470591-II

EAN: 5905378206830

**LED line PRIME Ceiling lamp LUNAR
22W 4000K 2200lm IP65 round**



LUNAR from LED line PRIME is a modern light source with a power of 22 W, which emits a light stream up to 2200 lm. It is characterized by colour temperature 4000 K, offering pleasant, neutral lighting. Its robust polycarbonate design provides high resistance to damage and IP65, which guarantees protection against moisture. Class D energy efficiency and light efficiency at 100 lm/W make it both economical and ecological.



Technical data

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5
Power	• 22 W
Voltage	• 220-240 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP65
IK protection rating	10
IEC protection class	II
Luminous efficacy	100
Luminous flux	2200
The lumen maintenance factor	96
Lifetime L70B50	50 000 h
Survival factor	0.9

Parameter	Value
Colour consistency in McAdam ellipses	≤6
Output current	0,106
Frequency of the supply voltage	50/60Hz
Fixture's diameter	300
Beam angle	120
LED type	SMD2835
LED quantity	200
Lifespan	50 000 h
Number of on/off cycles	50000
Lamp's warm-up time to 60%	1 s
Ambient temperature suitable for operation	-40÷45
Colour	White
Material (housing)	Polycarbonate
Material (cover)	polycarbonate


LED line PRIME

Code: 470591-II


EAN: 5905378206830

**LED line PRIME Ceiling lamp LUNAR
22W 4000K 2200lm IP65 round**

Technical drawing




Light distribution




Additional product photos


Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 470591-II

EAN: 5905378206830

**LED line PRIME Ceiling lamp LUNAR
22W 4000K 2200lm IP65 round**

Example application