

LED line PRIME

Code: 202733

EAN: 5905378202733

**FLOODLIGHT 3CCT (3K/4K/5K) 30W  
4200lm T2 IP66 PRIME**



The PRIME Floodlight 30W LED line is a modern device with high light efficiency, reaching up to 4200 lm at 30 W power. With energy efficiency of 140 lm/W, it minimises energy consumption and reduces operating costs. IP66 leak class provides resistance to adverse weather conditions, and IK08 protection level guarantees mechanical strength.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	5/7*
Power	• 30 W
Voltage	• 100-277 V AC
Correlated colour temperature	• 3000 K • 4000 K • 5000 K
Colour of the light	White
Colour rendering index Ra	70
IP protection rating	IP66
IK protection rating	08
IEC protection class	I
Luminous efficacy	140
Luminous flux	4200
The lumen maintenance factor	96
Lifetime L70B50	50 000 h

Parameter	Value
L80B* – difference B10–B50 ≈ 1% (according to LightingEurope) – negligible	35000 h
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Wire length	890 mm
Mounting type	surface
Frequency of the supply voltage	50/60Hz
Beam angle	70°155
LED type	SMD2835
Power Factor	0,9
Number of on/off cycles	50000
Ambient temperature suitable for operation	-40÷45
Height	43,5
Material (housing)	Aluminium
Material (cover)	Tempered glass


LED line PRIME

Code: 202733


EAN: 5905378202733

**FLOODLIGHT 3CCT (3K/4K/5K) 30W  
4200lm T2 IP66 PRIME**

**Technical drawing**





**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Width	252 mm
Height	54 mm
Length	213 mm
Weight	1 kg

**Bulk packaging**

Quantity	10
Width	4800 mm
Height	2850 mm
Length	100 mm
Volume	1,368 m3
Weight	10,35 kg
Comments	

**Europallet**

Quantity	200
Height	1710 mm
Quantity in layer	30
Number of layers	6
Bulk quantity	180
Weight	211,3 kg

---

LED line PRIME

Code: 202733

EAN: 5905378202733

**FLOODLIGHT 3CCT (3K/4K/5K) 30W  
4200lm T2 IP66 PRIME**

---

**Example application**