

LED line LITE

Code: 203921-AW3HAT

EAN: 5905378216679

Panel Backlit 2in1 40W 4000K 4000LM  
60x60 white emergency module 3h  
autotest LITE



Backlit panel 2in1 40W 4000K offers high light performance of 4,000 lumens, making it ideal for different applications. It is characterized by neutral light color (4000K), providing comfortable space lighting. The built-in emergency module guarantees up to 3 hours of operation in case of power outage, and the self-test function provides reliability.



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	autotest
Voltage	<ul style="list-style-type: none"><li>220-240 V AC</li></ul>
Luminous efficacy	100
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	4000
Colour consistency in McAdam ellipses	≤6
Warranty (years)	2
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	30 000 h
Frequency of the supply voltage	50/60Hz

Parameter	Value
Colour rendering index Ra	80
The lumen maintenance factor	96
Material (cover)	polystyrene
Material (housing)	Metal
Power Factor	0,9
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
IEC protection class	I
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Correlated colour temperature	<ul style="list-style-type: none"><li>4000 K</li></ul>
Power	<ul style="list-style-type: none"><li>40 W</li></ul>

LED line LITE

Code: 203921-AW3HAT

EAN: 5905378216679

**Panel Backlit 2in1 40W 4000K 4000LM  
60x60 white emergency module 3h  
autotest LITE**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

---

LED line LITE

Code: 203921-AW3HAT

EAN: 5905378216679

**Panel Backlit 2in1 40W 4000K 4000LM  
60x60 white emergency module 3h  
autotest LITE**

---

**Example application**