

LED line LITE

Code: 200869

EAN: 5905378200869

**DOWNLIGHT MOLLY 4000K 12W 1250lm square IP20 White LITE**



LED line LITE Downlight MOLLY 12W is a square model with a luminous flux of 1250 lumens, offering natural light at 4000K colour temperature. It is characterized by a minimalist design, making it an ideal choice for different interior arrangements. Made of durable polycarbonate, it ensures high durability and aesthetic appearance. Thanks to the IP20 leak class and high light efficiency, it works under different mounting conditions.



**Technical data**

Parameter	Value
Energy efficiency class 2019/2015	D
Warranty	3
Power	• 12 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 4000 K
Colour of the light	White
Colour rendering index Ra	80
IP protection rating	IP20
IEC protection class	II
Luminous efficacy	105
Luminous flux	1250
The lumen maintenance factor	96
Lifetime L70B50	30 000 h

Parameter	Value
Survival factor	0.9
Colour consistency in McAdam ellipses	≤6
Frequency of the supply voltage	50/60Hz
LED type	SMD LED 2835
LED quantity	56
Power Factor	0,5
Number of on/off cycles	20000
Ambient temperature suitable for operation	-20÷40
For indoor use	Inside
Mounting hole diameter	120-135
Height	26
Colour	White
Material (housing)	Polycarbonate


LED line LITE

Code: 200869


EAN: 5905378200869

**DOWNLIGHT MOLLY 4000K 12W 1250lm square IP20 White LITE**

**Technical drawing**




**Light distribution**



**Additional product photos**



**Logistics data**



**Single packaging**

Quantity	1
Width	145 mm
Height	26 mm
Length	145 mm
Weight	0,173 kg

**Bulk packaging**

Quantity	60
Width	390 mm
Height	322 mm
Length	473 mm
Volume	0,043 m3
Weight	12,1 kg

**Europallet**

Quantity	1800
Height	1,7 m
Quantity in layer	360
Number of layers	5
Bulk quantity	30
Weight	393 kg

LED line LITE

Code: 200869

EAN: 5905378200869

**DOWNLIGHT MOLLY 4000K 12W 1250lm  
square IP20 White LITE**

**Example application**

