

LED line LITE

Code: 200869

EAN: 5905378200869

LED line LITE Downlight MOLLY 12W
1250lm 4000K square



Technical data

Parameter	Value
Luminous efficacy	105 lm/W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1250 lm
Colour consistency in McAdam ellipses	≤6
IP protection rating	IP20
Warranty (years)	3
Survival factor	0.9
Lifetime L70B50	30 000
Weight	132.2 g
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96 %
Material (housing)	Polycarbonate
LED type	SMD LED 2835


Parameter	Value
LED quantity	56
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	20000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-20÷40 °C
Mounting hole diameter	120-135 mm
For indoor use	Inside
IEC protection class	II
Length	145 mm
Width	145 mm
Height	26 mm
Power	• 12 W
Voltage	• 170-260 V AC
Correlated colour temperature	• 4000 K

LED line LITE Downlight MOLLY 12W
1250lm 4000K square




Dimensions

Light distribution

Additional product photos



Logistics data



Single packaging

Width	145 mm
Height	26 mm mm
Length	145 mm mm
Weight	0,13 kg kg

Bulk packaging

Number of pieces/tape in meters pack zb	60 szt.
Width	480 mm mm
Height of collective packaging	285 mm
Length	320 mm mm
Weight	12,1 kg kg
Volume	0,043 m3 m3

Europallet

Quantity collective euro pallet	1440 szt.
Weight of a euro pallet	290,4 kg
Pallet height	1710 mm
Quantity in 1 layer	240 szt.
Number of layers	6

LED line LITE

Code: 200869

EAN: 5905378200869

**LED line LITE Downlight MOLLY 12W
1250lm 4000K square**

Example application



zdjęcie-realizacji.png