

LED line PRIME LED bulb E14 7W 4000K 1000lm 170-250V C37



Manufacturer issues a 5-year warranty for this product.



FLICKER FREE™ system guarantees no harmful flickering effect and ensures safety for users' eyesight.



Beam angle



LED type



The structural design of this product ensures effective heat dissipation.



Voltage range and voltage type



Lamp type




Lifespan

Parameter	Value
Luminous efficacy	142lm/W
Power	7 W
Colour of the light	White
Energy efficiency class 2019/2015	D
Luminous flux	1000 lm
Correlated colour temperature	4000 K
Colour consistency in McAdam ellipses	≤6
IP protection rating	20
Warranty (years)	5
Dimmable function	No
Survival factor	0.9
Lifetime L70B50	30 000
Supply voltage range and voltage type	170-250V AC
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	White
The lumen maintenance factor	96
Lamp's type	C37
Lamp's diameter	37
Beam angle	220 °

Parameter	Value
LED type	SMD2835
Lifespan	30000
Power Factor	0,5
Number of on/off cycles	50000
Colour consistency in McAdam ellipses	≤6
For indoor use	Inside
Full box quantity	100 pc
Lamp's warm-up time to 60%	1
Height	111 mm
Master carton weight (kg)	7
Angle for useful luminous flux (EPREL)	Sphere 360 degrees
Is the product equipped with an integrated light source? (EPREL)	No
Non-directional or directional light source (EPREL)	NDLS
Is this product a light source? (EPREL)	Yes
Mains or non- mains light source (EPREL)	MLS
Connected light source (EPREL)	No
Colour-tuneable light source (EPREL)	No
Total luminous flux (EPREL)	1 000
On-mode power P _{on} (EPREL)	7
Useful luminous flux Φ _{use} (EPREL)	1 000


Material (cover)	glass	Beam angle in degrees (EPREL)	220
Material (housing)	Ceramic		

Single packaging



1

Bulk packaging



Europallet

