

LED line PRIME


Code: 200180-AW3HAT

EAN: 5905378213579

Panel Backlit 40W 4000K 4800lm
60x60 Emergency module 3h autotest
PRIME



The 40 W Backlit PRIME panel and 4800 lm light stream are a perfect solution for modern interiors. Its neutral colour of light 4000 K provides pleasant lighting, and a wide lighting angle of 120° guarantees uniform distribution of light. The product is equipped with an automatic emergency module that runs for 3 hours.



Technical data

Parameter	Value
Operating time in emergency mode	3 h
Emergency module test	Autotest
Voltage	• 220-240 V AC
Luminous efficacy	120
Colour of the light	White
Energy efficiency class 2019/2015	E
Luminous flux	4800
Colour consistency in McAdam ellipses	≤6
Warranty (years)	5
IP protection rating	IP20
Dimmable function	PWM
Survival factor	0.9
Lifetime L70B50	75 000 h
Frequency of the supply voltage	50/60Hz
Colour rendering index Ra	80
Colour	white
The lumen maintenance factor	96

Parameter	Value
Beam angle	120
Material (cover)	polystyrene
Material (housing)	Aluminium
LED type	SMD LED 2835
LED quantity	48
Power Factor	0,9
Number of on/off cycles	25000
Colour consistency in McAdam ellipses	≤6
Ambient temperature suitable for operation	-25÷45
For indoor use	Inside
IEC protection class	II
IK protection rating	02
Lamp's warm-up time to 60%	1 s
Energy class	A+
Correlated colour temperature	• 4000 K
Power	• 40 W

LED line PRIME

Code: 200180-AW3HAT



EAN: 5905378213579

**Panel Backlit 40W 4000K 4800lm
60x60 Emergency module 3h autotest
PRIME**


Technical drawing

Light distribution


Additional product photos




Logistics data



Single packaging



Bulk packaging



Europallet

LED line PRIME

Code: 200180-AW3HAT

EAN: 5905378213579

**Panel Backlit 40W 4000K 4800lm
60x60 Emergency module 3h autotest
PRIME**

Example application

